

RF:sj 11/6/01 128.822PAT

PATENT

a cylindrical distributor housing having a cylinder axis arranged horizontally and transverse to the pulp web;

the distributor housing having an inlet defined therein for the cellulose pulp;

a rotating feed screw having an axis of rotation parallel to the cylinder axis of the distributor housing being designed to feed pulp from the inlet and along an entire length of the distributor housing in a direction of its cylinder axis; and

the distributor housing having outlets defined therein and arranged substantially along a generatrix in a jacket surface of the distributor housing, the outlets having holes arranged along the generatrix in the jacket surface of the distributor housing, the holes having a hole-diameter (d) and being arranged at a distance (x) from each other.

12. The distributor device according to claim 11 wherein the distance (x) exceeds the hole-diameter (d).

13. The distributor device according to claim 11 wherein the hole-diameter (d) is in the range of 20 millimeters to 60 millimeters.

RF:sj 11/6/01 128.822PAT

PATENT

14. The distributor device according to claim 13 wherein the hole-diameter (d) increases continuously from the inlet of the distributor housing.

15. The distributor device according to claim 13 wherein the holes are distributed evenly across the entire width of the pulp web formed from the distributor device.

16. The distributor device according to claim 12 wherein the distance (x) is between 40 millimeters and 90 millimeters and the distance (x) is at least 150% of the hole-diameter (d).

17. The distributor device according to claim 11 wherein the holes are arranged in a lowest part of the jacket surface of the distributor housing directed substantially straight down from the distributor housing and within an area of rotation in a range of ± 45 degrees.

RF:sj 11/6/01 128.822PAT

PATENT

18. The distributor device according to claim 11 wherein a feed-screw has a screw thread with crests being sweepable across the holes at a predefined distance (y) from the holes in the jacket surface of the distributor housing, the distance (y) is in a range of 5 millimeter to 20 millimeters.

19. The distributor device according to claim 18 wherein the feed screw has a core with a diameter increasing continuously from the inlet and an annular gap around the feed screw, into which the pulp is conveyed, decreases continuously from the inlet of the distributor housing.

20. The distributor device according to Claim 18 wherein the feed-screw has a decreasing thread pitch on a screw blade.

21. The distributor device according to claim 11 wherein the hole-diameter (d) is in the range of 35 millimeters to 45 millimeters.

Date of Mailing: 6 November 2001

RF:sj 11/6/01 128.822PAT

PATENT

22. The distributor device according to claim 12 wherein the distance (x) is between 40 millimeters and 90 millimeters and the distance (x) is at least 150% of the hole-diameter (d).

a¹
23. The distributor device according to claim 12 wherein the distance (x) is between 70 millimeters and 80 millimeters and the distance (x) is at least 150% of the hole-diameter (d).

24. The distributor device according to claim 11 wherein a feed-screw has a screw thread with crests being sweepable across the holes at a predefined distance (y) from the holes in the jacket surface of the distributor housing, the distance (y) is in a range of 8 millimeters to 12 millimeters.

25. The distributor device according to claim 11 wherein the apparatus treating the cellulose pulp is a wash press.
